


**ENVIRONMENTAL CONTROL SYSTEM** 

# Ducted environmental control system

/ Model ECS-08TC (2018)





**Cooling Capacity** 

/ 130 °F (54.4 °C)

Design Ambient Cooling

/ 130 °F (54.4 °C)

**Maximum Ambient Cooling** 

These units have been designed and tested for use on shelters, vans, and trailers that are subject to demanding transport and environmental conditions. All systems can be modified to meet your specific requirements.

MilAIR's standard product line of unitary ducted systems provide complete environmental control including cooling, heating, ventilation, dehumidification, and filtering.

Please contact sales@milairinc.com for additional information and options.



# Ducted environmental control system

/ Model ECS-08TC (2018)

## **Standard Features**

- Sealed Motors
- Washable Metal Return Air Filter
- Refrigerant Access Valves
- Refrigerant Sight Glass
- Condensation Drain Kit
- 6 Inch Supply/Return Air Duct Interface
- Condenser Coil Corrosion
  Protection

# Options

- Finish to Specification
- Ground Support Hand Cart
- Remote Control Panel
- Power Cord
- Insulated Supply/Return Ducts

#### **Characteristics**

Refrigerant	R407c
Compressor	Hermetic Rotary Type
Evaporator Coil	Alum. Fin/Copper Tube
Condenser Coil	Alum. Micro-Channel
Circulating Fan	Motorized Impeller
Condenser Fan	Motorized Impeller
Size (L x W x H)	29.2" x 21.5" x 19.6" 74.2 cm x 54.6 cm x 49.8 cm
Frame & Panels	Aluminum
System Weight	116 lbs. (52.6 kg)
Local Control Panel	Auto/Vent, Control Power C/B Thermostat Temp Control

## Performance

Cooling Capacity	7,500 Btu/h @ 50 Hz	
Design Ambient Cooling	130 °F (54.4 °C)	
Maximum Ambient Cooling	130 °F (54.4 °C)	
Minimum Ambient Cooling	40 °F (4.4 °C)	
Design Return Air Temperature	85 °F (29.4 °C) db	
Supply Air Flow Rate	275 CFM (8.49 CMM)	
Heating Capacity	5,800 Btu/hr. (1.7 kW)	
Minimum Ambient Heating	-40 °F (-40 °C)	
Evaporator Static Pressure	1.2 Inch Water	

# Electrical

Input Voltage	230 VAC
Number of Phases	1Ф
Frequency	50/60 Hz
Max Power Draw	2.0 kW
Wires	2-Wire + GND

# Trusted Partner.

# **Horstman United States**

44215 Phoenix Drive, Sterling Heights, MI 48314 P +1 (586) 737-2100 E sales@milairinc.com

Details provided about the properties and usability of the products are purely for information purposes and do not constitute a guarantee of these characteristics. The extent of goods delivered is determined by the subject matter of the specific contract. No liability accepted for errors or omissions. Subject to technical alterations. © HORSTMAN 2023